



Product Specification

2 MP LED Array Dome IP Camera





ALS-65D-DR 2MP Indoor Dome IP Cameras

Key Features:

- 2 Mega Pixel CMOS LED Array Indoor Dome IP Camera
- Support high definition resolution 2 Mega pixel 25 fps @1920*1080
- Delay Time Less than 200 MSec (0.2 second) in LAN.
- ONVIF compatible
- Standard H.265/ H.264 Video Compression
- Built-in high performance IR LED with IR cut
- Exceptional night surveillance Remove noise and ghost image with DNR
- Day & night with ICR(Infrared cutter removal)
- Built-in Web Server, support IE browser monitor, IE configure, IE upgrade
- IP Based Filtering and built-in Firewall Support
- The bit rate adjusting assures the real-time transmission of audio
- On Internet User Management support three level user & password
- Alarm I/O support Motion Detection, date, time, event trigger
- Support local and Remote recording
- Support Remote Configuration and Update
- Support image capture
- Support image mask
- Support Auto Iris Interface
- Support video loop back
- Standard PoE 802.3af

| Model | ALS-65D-DR |
|---|---|
| Hardware Compression: | H.265, H.264 |
| IR Distance: | 30M |
| Audio Interface: | Optional |
| Network Interface: | 10/100MBaseT,RJ-45 Ethernet |
| Protocols: | PPPoE, DHCP,TCP/IP, SNMP, HTTP, UDP, RTP/RTCP, RTSP,UPNP, SMTP, FTP, SIP, DDNS, DNS, Multicast |
| Security: | Multi-user grade 128bit encrypt arithmetic |
| Lens: | 3.6-12mm lens fixed, as per requirement |
| Lens Mount: | M12 |
| Camera White Balance: | Auto |
| Image Sensor: | 1/3" Progressive Scan CMOS |
| Minimum Illumination: | 0.1Lux/F1.2; B/W 0.001Lux/F1.2, 0Lux/F1.2 IR ON |
| Resolution: | 1080P |
| Dual Stream: | 25fps 1920*1080(1080P), 25fps 1280*960(960P), 25fps 1280*760(720P), 25fps 352*288(CIF), 25fps 176*144(QCIF) |
| WDR Support: | Yes |
| Bit range rate: | 1M 8Mbps/1M 16Mbps,CBR/VBR Variable |
| Image Settings: | Image Flip, Brightness, Contrast, Saturation, Hue, Exposal Control, AGC, AWB, BLC, Privacy Mask, Motion Detection |
| Electronic Shutter Speed: | 1/50s-1/4,000 sec |
| Frame Rate: | 25fps 1920*1080(1080P), 25fps 1280*960(960P), 25fps 1280*760(720P), 25fps 352*288(CIF), 25fps 176*144(QCIF) |
| Browsers: | Internet Explorer, Mozilla, Google Chrome, Safari |
| Built in Double Digital Signal Processing: | Yes |
| Video loop back: | Yes |
| DDNS: | Yes |
| Motion Detection: | Yes |
| Alarm IO: | 1 in 1 out |
| Auto Iris: | Yes |
| Video S/N Ratio: | More Than 50dB |
| Temperature: | -10°C--+60°C |
| Humidity: | <95%RH |
| Power Supply: | 12V, PoE 802.3af (optional) |
| Power: | <12W |
| Net Weight: | 0.22KG |
| Gross Weight: | 0.52KG |
| Make: | Airlinx Systems |