



Product Specification

2 Mega Pixel LED IP Camera





ALS150HS-IR-2MP Mega Pixel Waterproof Box IP Camera

Key Features:

- 2 Mega Pixel CMOS LED Waterproof IP Camera
- Support high definition resolution 2 Mega pixel 30 fps @1920*1080
- Delay Time Less than 200 MSec (0.2 second) in LAN.
- ONVIF compatible
- Standard H.265, H.264 Video Compression
- Built-in high performance IR LED with IR cut
- Exceptional night surveillance Remove noise and ghost image with DNR
- Day & night with ICR(Infrared cutter removal)
- Built-in Web Server, support IE browser monitor, IE configure, IE upgrade
- IP Based Filtering and built-in Firewall Support
- The bit rate adjusting assures the real-time transmission of audio on Internet User Management support three level user & password
- Alarm I/O support Motion Detection, date, time, event trigger
- Support local and Remote recording
- Support Remote Configuration and Update
- Support image capture
- Support image mask
- Support Auto Iris Interface
- Support video loop back
- Support Tow way Audio
- IEEE 802.3af PoE

Model	ALS150HS
Hardware Compression:	H.26H, H.264
IR Distance:	30M
Network Interface:	10/100MBaseT,RJ-45 Ethernet
Protocols:	PPPoE, DHCP,TCP/IP, SNMP, HTTP, UDP, RTP/RTCP, RTSP,UPNP, SMTP, FTP, SIP, DDNS, DNS, Multicast
Security:	Multi-user grade 128bit encrypt arithmetic
Motorized Lens:	3.6-16mm lens fixed, as per requirement
Lens Mount:	C/CS Mount
Camera White Balance:	Auto
Image Sensor:	1/ 2.7" Progressive Scan CMOS
Minimum Illumination:	0.002Lux/F1.2; B/W 0. 001Lux/F1.2, 0Lux/F1.2 IR ON
Resolution:	1920*1080P
Dual Stream:	30fps 1920*1080 (1080P), 30fps 1280*960(960P), 3fps 1280*720(CIF)
WDR Support:	Yes
Digital Noise Reduction:	2D / 3D
Bit range rate:	1M 8Mbps/1M 16Mbps,CBR/VBR Variable
Corridor Mode:	9:16
Image Settings:	Image Flip, Brightness, Contrast, Saturation, Hue, Exposal Control, AGC, AWB, BLC, Privacy Mask,
Defog:	Supported
Smart Feature:	Motion detection, Crossing line, Intrusion , Face detection, People counting, Defocus, Scene Change
Electronic Shutter Speed:	1/50s-1/4,000 sec
Frame Rate:	30fps 1920*1080 (1080P), 30fps 1280*960(960P), 3fps 1280*720(CIF)
Browsers:	Internet Explorer, Mozilla, Google Chrome, Safari
Built in Double Digital Signal Processing:	Yes
Region of Interest:	Supported
Video loop back:	Yes
DDNS:	Yes
Motion Detection:	Yes
Alarm IO:	1 in 1 out
Auto Iris:	Yes
Video S/N Ratio:	More Than 50dB
Temperature:	-10°C--+60°C
Humidity:	<95%RH
Power Supply:	PoE 802.3af
Power:	<15W
Net Weight:	.30KG
Gross Weight:	.60KG
Make:	Airlinx Systems
Accessories:	IP66 Standard Weather proof Housing and Bracket