



Product Specification

2 MP IR HD Network Dome Camera





ALS72CM Indoor Mega Pixel vandal proof IP Camera

Key Features:

- 2 Mega Pixel CMOS LED Vandal Proof IP Camera
- Support high definition resolution 2 Mega pixel
- H.264/MJPEG Video Compression
- Delay Time Less than 200 MSec (0.2 second) in LAN.
- TF card Supported
- ONVIF compatible
- Standard H.265/ H.264 Video Compression
- Built-in high performance IR LED
- Support heart Beat
- Exceptional night surveillance Remove noise and ghost image with DNR
- Day & night with ICR (Infrared cutter removal)
- Built-in Web Server, support IE browser monitor, IE configure, IE upgrade
- IP Based Filtering and built-in Firewall Support
- The bit rate adjusting assures the real-time transmission of audio on Internet User Management support three level user & password
- Alarm I/O support Motion Detection, date, time, event trigger
- Support local and Remote recording
- Support Remote Configuration and Update
- Support image capturing
- Support image mask
- Support Auto Iris Interface
- Support video loop back
- PoE Support

Model	ALS72CM
Hardware Compression:	H.265/H.264
CPU:	HI3510
FLASH:	64M
DRAM:	256M
System:	Embedded Linux
Resolution:	1920*1080P
Watermark Video:	Yes
IR Distance:	30M
Network Interface:	10/100MBaseT,RJ-45 Ethernet
Protocols:	PPPoE, DHCP,TCP/IP,HTTP,UDP,RTP/RTCP,RTSP,UPNP,SMTP,FTP, SIP,DDNS,DNS, Multicast
Communication Port:	1 RS-485(PTZ),1RS-232
Security:	Multi-user grade 128bit encrypt arithmetic
Lens:	Auto focus Motorized Lens 2.8 to 8mm
Lens Optional:	YES
Lens :	2.8 to 12mm Motorized Zoom Lens
Camera White Balance:	Auto
Image Sensor:	1/3" Progressive Scan CMOS
Minimum Illumination:	0.01lux; B/W : 0.001lux
Effective Pixels / Resolution:	1920(H)x1080(V)
Bit Range Rate:	1M 16Mbps/1M 20Mbps CBR/VBR variable
Image Settings:	Image Flip, Brightness, Contrast, Saturation, Hue, Exposal Control, AGC, AWB, BLC, Privacy Mask, Motion Detection
Electronic Shutter Speed:	1/50s —1/50,000 sec.
Frame Rate:	25 fps (1920*1080) , 25 fps (1280*960), 25 fps (1280*720)
Browser:	IE, Chrome, Mozilla
Built in Double Digital Signal Processing:	Yes
Video loop back:	Yes
DDNS:	Yes
Motion Detection:	Yes
Alarm IO:	1 in 1 out
Audio Interface:	Optional
Auto Iris:	Yes
Video S/N Ratio:	More Than 50dB
Analog Video Output:	1Vp-p Composite Output (75 Ohm, BNC)
Temperature:	-10°C--+60°C
Humidity:	<95%RH
Voltage:	DC12V/2A , POE
Power:	<15W
Product Dimension:	232 (L) *123(W)* 116(H) mm
Net Weight:	0.7 KG
Make:	Airlinx Systems
Accessories:	IP66 Water & Weather proof Housing and Bracket