



# Product Specification

## 3 MP LED Array Indoor Dome IP Camera





## ALS-91D-IR 3MP IndoorDome IP Cameras

### Key Features:

- 3 Mega Pixel CMOS LED Array Indoor IP Camera
- Support high definition resolution 3 Mega pixel 25 fps @2048\*1536
- Delay Time Less than 200 MSec (0.2 second) in LAN.
- ONVIF compatible
- Standard H.265, H.264 Video Compression
- Built-in high performance IR LED with IR cut
- Exceptional night surveillance Remove noise and ghost image with DNR
- Day & night with ICR(Infrared cutter removal)
- Built-in Web Server, support IE browser monitor, IE configure, IE upgrade
- IP Based Filtering and built-in Firewall Support
- The bit rate adjusting assures the real-time transmission of audio on Internet User Management support three level user & password
- Alarm I/O support Motion Detection, date, time, event trigger
- Support local and Remote recording
- Support Remote Configuration and Update
- Support image capture
- Support image mask
- Support Auto Iris Interface
- Support video loop back
- Standard PoE 802.3af



Model	ALS-91D-IR
Hardware Compression:	H.265, H.264
IR Distance:	30M
Audio Interface:	Optional
Network Interface:	10/100MBaseT,RJ-45 Ethernet
Protocols:	PPPoE, DHCP,TCP/IP, SNMP, HTTP, UDP, RTP/RTCP, RTSP,UPNP, SMTP, FTP, SIP, DDNS, DNS, Multicast
Security:	Multi-user grade 128bit encrypt arithmetic
Lens:	3.6-12mm lens fixed, as per requirement
Lens Mount:	M12
Camera White Balance:	Auto
Image Sensor:	1/3" Progressive Scan CMOS
Minimum Illumination:	0.1Lux/F1.2; B/W 0.001Lux/F1.2, 0Lux/F1.2 IR ON
Resolution:	1536P
Dual Stream:	25fps 2048*1536(1536), 25fps 1280*960(960P), 25fps 1280*760(720P), 25fps 352*288(CIF), 25fps 176*144(QCIF)
WDR Support:	Yes
Bit range rate:	1M 8Mbps/1M 16Mbps,CBR/VBR Variable
Image Settings:	Image Flip, Brightness, Contrast, Saturation, Hue, Exposal Control, AGC, AWB, BLC, Privacy Mask, Motion Detection
Electronic Shutter Speed:	1/50s-1/4,000 sec
Frame Rate:	25fps 2048*1536(1536), 25fps 1280*960(960P), 25fps 1280*760(720P), 25fps 352*288(CIF), 25fps 176*144(QCIF)
Browsers:	Internet Explorer, Mozilla, Google Chrome, Safari
Built in Double Digital Signal Processing:	Yes
Video loop back:	Yes
DDNS:	Yes
Motion Detection:	Yes
Alarm IO:	1 in 1 out
Auto Iris:	Yes
Video S/N Ratio:	More Than 50dB
Temperature:	-10°C--+60°C
Humidity:	<95%RH
Power Supply:	12V, PoE 802.3af (optional)
Power:	<12W
Net Weight:	0.22KG
Gross Weight:	0.52KG
Make:	Airlinx Systems